

LIGHT, VENTILATION & EGRESS DATA

OPENING SPECIFICATIONS

THERMO-TECH 7400 SLIDER/2-PANEL XO

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TS-3624	14 1/2"	19 5/16"	1.94	3.46
TS-4824	20 1/2"	19 5/16"	2.75	4.98
TS-6024	26 1/2"	19 5/16"	3.55	6.49
TS-7224	32 1/2"	19 5/16"	4.35	8.01
TS-3636	14 1/2"	31 5/16"	3.15	5.74
TS-4836	20 1/2"	31 5/16"	4.45	8.26
TS-6036 E	26 1/2"	31 5/16"	5.76	10.78
TS-7236 E	32 1/2"	31 5/16"	7.06	13.29
TS-3642	14 1/2"	37 5/16"	3.75	6.88
TS-4842	20 1/2"	37 5/16"	5.31	9.90
TS-6042 E	26 1/2"	37 5/16"	6.86	12.92
TS-7242 E	32 1/2"	37 5/16"	8.42	15.94
TS-3644	14 1/2"	39 5/16"	3.95	7.16
TS-4844	20 1/2"	39 5/16"	5.59	10.30
TS-4944 E	21"	39 5/16"	5.73	10.69
TS-6044 E	26 1/2"	39 5/16"	7.23	13.44
TS-7244 E	32 1/2"	39 5/16"	8.87	16.58
TS-3648	14 1/2"	43 5/16"	4.36	8.02
TS-4848 E	20 1/2"	43 5/16"	6.16	11.54
TS-6048 E	26 1/2"	43 5/16"	7.97	15.06
TS-7248 E	32 1/2"	43 5/16"	9.77	18.58
TS-3654	14 1/2"	49 5/16"	4.96	9.16
TS-4854 E	20 1/2"	49 5/16"	7.02	13.18
TS-6054 E	26 1/2"	49 5/16"	8.07	17.20
TS-7254 E	32 1/2"	49 5/16"	11.13	21.22
TS-3660	14 1/2"	55 5/16"	5.57	10.30
TS-4860 E	20 1/2"	55 5/16"	7.87	14.82
TS-6060 E	26 1/2"	55 5/16"	10.17	19.34
TS-7260 E	32 1/2"	55 5/16"	12.48	23.86

THERMO-TECH 7400 3-LITE SLIDER/XOX 1/4" X 1/2" X 1/4"

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TS 3-7242	14 1/2"	37 5/16"	3.75 x 2	14.90
TS 3-7244	14 1/2"	39 5/16"	3.95 x 2	15.79
TS 3-7248	14 1/2"	43 5/16"	4.36 x 2	17.44
TS 3-7254	14 1/2"	49 5/16"	4.96 x 2	19.92
TS 3-7260	14 1/2"	55 5/16"	5.56 x 2	22.40
TS 3-8442	17 1/2"	37 5/16"	4.53 x 2	17.98
TS 3-8444	17 1/2"	39 5/16"	4.77 x 2	18.97
TS 3-8448	17 1/2"	43 5/16"	5.29 x 2	20.96
TS 3-8454	17 1/2"	49 5/16"	5.99 x 2	23.94
TS 3-8460	17 1/2"	55 5/16"	6.72 x 2	26.92
TS 3-9642	20 1/2"	37 5/16"	5.31 x 2	21.00
TS 3-9644	20 1/2"	39 5/16"	5.59 x 2	22.16
TS 3-9648	20 1/2"	43 5/16"	6.16 x 2	24.48
TS 3-9654	20 1/2"	49 5/16"	7.01 x 2	27.96
TS 3-9660	20 1/2"	55 5/16"	7.87 x 2	31.43

E= Denotes 5.7 square feet or greater clear opening. Verify local or state egress opening sizes with your local building inspector.



THERMO-TECH 2600 CASEMENT

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TC-2036	7.625	30.5	1.61	2.76
TC-2042	7.625	36.5	1.93	3.89
TC-2048	7.625	42.5	2.25	4.45
TC-2056	7.625	50.5	2.67	4.64
TC-2060	7.625	54.5	2.88	5.01
TC-2064	7.625	58.5	3	5.3
TC-2072	7.625	66.5	3.5	6.1

THERMO-TECH 2600 CASEMENT-24"

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TC-2436	11.625	30.5	2.46	3.58
TC-2442	11.625	36.5	2.94	4.31
TC-2448	11.625	42.5	3.43	5.04
TC-2456	11.625	50.5	4.07	6.01
TC-2460	11.625	54.5	4.39	6.50
TC-2464	11.625	58.5	4.7	6.9
TC-2472	11.625	66.5	5.3	7.9

THERMO-TECH 2600 CASEMENT-28"

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TC-2836	15.625	30.5	3.30	4.55
TC-2842	15.625	36.5	3.96	5.30
TC-2848 E*	20.125	42.5	5.93	6.19
TC-2848	15.625	42.5	4.61	6.19
TC-2856 E*	20.125	50.5	7.05	7.39
TC-2856	15.625	50.5	5.47	7.39
TC-2860 E*	20.125	54.5	7.61	7.98
TC-2860	15.625	54.5	5.91	7.98
TC-2864 E*	20.125	58.5	8.1	8.5
TC-2864	15.625	58.5	6.3	8.5
TC-2872 E*	20.125	66.5	9.2	9.7
TC-2872	15.625	66.5	7.2	9.7

THERMO-TECH 2600 CASEMENT-32"

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TC-3236	19.625	30.5	4.15	5.22
TC-3242	19.625	36.5	4.97	5.40
TC-3248 E	24.125	42.5	7.12	7.34
TC-3248	19.625	42.5	5.79	7.34
TC-3256	19.625	50.5	6.88	8.94
TC-3260	19.625	54.5	7.42	9.47
TC-3264 E*	24.125	58.5	9.7	10.1
TC-3264	19.625	58.5	7.9	10.1
TC-3272 E*	24.125	66.5	11.1	11.5
TC-3272	19.625	66.5	9	11.5

THERMO-TECH 2600 CASEMENT-36"

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TC-3636	23.625	30.5	5.00	6.04
TC-3642 E	23.625	36.5	5.98	7.27
TC-3648 E	23.625	42.5	6.97	8.50
TC-3656 E	23.625	50.5	8.2	10.1
TC-3660 E	23.625	54.5	8.9	10.9
TC-3664 E	23.625	58.5	9.5	11.7
TC-3672 E	23.625	66.5	10.9	13.4

E*=Egress Hardware used

E= Denotes 5.7 square feet or greater clear opening. Verify local or state egress opening sizes with your local building inspector. Casement Max square footage: 17.6 square feet.



Energy Star® qualified in all four climate zones.

LIGHT, VENTILATION & EGRESS DATA

OPENING SPECIFICATIONS

THERMO-TECH 7100 SINGLE-HUNG

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TSH-2036	15.312	12	1.27	2.61
TSH-2040	15.312	14	1.48	3.00
TSH-2042	15.312	15	1.59	3.20
TSH-2048	15.312	18	1.91	3.78
TSH-2052	15.312	20	2.12	4.18
TSH-2056	15.312	22	2.33	4.57
TSH-2060	15.312	24	2.55	4.96
TSH-2064	15.312	26	2.76	5.35
TSH-2065	15.312	26.5	2.81	5.45
TSH-2072	15.312	30	3.19	6.14
TSH-2436	19.312	12	1.60	3.35
TSH-2440	19.312	14	1.87	3.85
TSH-2442	19.312	15	2.01	4.10
TSH-2448	19.312	18	2.41	4.86
TSH-2452	19.312	20	2.68	5.36
TSH-2456	19.312	22	2.95	5.86
TSH-2460	19.312	24	3.21	6.37
TSH-2464	19.312	26	3.48	6.87
TSH-2465	19.312	26.5	3.55	7.00
TSH-2472	19.312	30	4.02	7.88
TSH-2836	23.312	12	1.94	4.09
TSH-2840	23.312	14	2.26	4.70
TSH-2842	23.312	15	2.42	5.01
TSH-2848	23.312	18	2.91	5.93
TSH-2852	23.312	20	3.23	6.54
TSH-2856	23.312	22	3.56	7.16
TSH-2860	23.312	24	3.88	7.77
TSH-2864	23.312	26	4.20	8.39
TSH-2865	23.312	26.5	4.29	8.54
TSH-2872	23.312	30	4.85	9.62
TSH-3036	25.3125	12	2.1	4.4
TSH-3040	25.3125	14	2.5	5.1
TSH-3042	25.3125	15	2.6	5.4
TSH-3048	25.3125	18	3.1	6.4
TSH-3052	25.3125	20	3.5	7.1
TSH-3056	25.3125	22	3.8	7.8
TSH-3060	25.3125	24	4.2	8.4
TSH-3064	25.3125	26	4.5	9.1
TSH-3065	25.3125	26.5	4.6	9.3
TSH-3072	25.3125	30	5.2	10.4
TSH-3236	27.312	12	2.27	4.83
TSH-3240	27.312	14	2.65	5.55
TSH-3242	27.312	15	2.84	5.91
TSH-3248	27.312	18	3.41	7.00
TSH-3252	27.312	20	3.79	7.73
TSH-3256	27.312	22	4.17	8.45
TSH-3260	27.312	24	4.55	9.18
TSH-3264	27.312	26	4.93	9.91
TSH-3265	27.312	26.5	5.02	10.09
TSH-3272	27.312	30	5.69	11.36

THERMO-TECH 7100 SINGLE-HUNG

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TSH-3636	31.312	12	2.60	5.56
TSH-3640	31.312	14	3.04	6.40
TSH-3642	31.312	15	3.26	6.82
TSH-3648	31.312	18	3.91	8.08
TSH-3652	31.312	20	4.34	8.91
TSH-3656	31.312	22	4.78	9.75
TSH-3660	31.312	24	5.21	10.59
TSH-3664	31.312	26	5.65	11.42
TSH-3665 E	31.312	26.5	5.76	11.63
TSH-3672 E	31.312	30	6.52	13.10
TSH-4036	35.312	12	2.94	6.30
TSH-4040	35.312	14	3.43	7.25
TSH-4042	35.312	15	3.67	7.73
TSH-4048	35.312	18	4.41	9.15
TSH-4052	35.312	20	4.90	10.10
TSH-4056	35.312	22	5.39	11.04
TSH-4060 E	35.312	24	5.88	11.99
TSH-4064 E	35.312	26	6.37	12.94
TSH-4065 E	35.312	26.5	6.49	13.18
TSH-4072 E	35.312	30	7.35	14.84
TSH-4436	39.312	12	3.27	7.04
TSH-4440	39.312	14	3.82	8.10
TSH-4442	39.312	15	4.09	8.63
TSH-4448	39.312	18	4.91	10.22
TSH-4452	39.312	20	5.46	11.28
TSH-4456	39.312	22	6.00	12.34
TSH-4460 E	39.312	24	6.55	13.40
TSH-4464 E	39.312	26	7.09	14.46
TSH-4465 E	39.312	26.5	7.23	14.72
TSH-4472 E	39.312	30	8.19	16.58
TSH-4836	43.312	12	3.60	7.78
TSH-4840	43.312	14	4.21	8.95
TSH-4842	43.312	15	4.51	9.54
TSH-4848	43.312	18	5.41	11.29
TSH-4852	43.312	20	6.01	12.46
TSH-4856	43.312	22	6.61	13.63
TSH-4860 E	43.312	24	7.21	14.80
TSH-4864 E	43.312	26	7.82	15.97
TSH-4865 E	43.312	26.5	7.97	16.27
TSH-4872 E	43.312	30	9.02	18.31

E= Denotes 5.7 square feet or greater clear opening. Verify local or state egress opening sizes with your local building inspector.



LIGHT, VENTILATION & EGRESS DATA

OPENING SPECIFICATIONS

THERMO-TECH 7100 SINGLE-HUNG COTTAGE STYLE

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TSHCT-2048	15.312	12.5	1.32	3.78
TSHCT-2052	15.312	14.5	1.54	4.18
TSHCT-2056	15.312	16.5	1.75	4.57
TSHCT-2060	15.312	18.5	1.96	4.96
TSHCT-2448	19.312	12.5	1.67	4.86
TSHCT-2452	19.312	14.5	1.94	5.36
TSHCT-2456	19.312	16.5	2.21	5.86
TSHCT-2460	19.312	18.5	2.48	6.37
TSHCT-2848	23.312	12.5	2.02	5.93
TSHCT-2852	23.312	14.5	2.34	6.54
TSHCT-2856	23.312	16.5	2.67	7.16
TSHCT-2860	23.312	18.5	2.99	7.77
TSHCT-3048	25.3125	12.5	2.1	6.4
TSHCT-3052	25.3125	14.5	2.5	7.1
TSHCT-3056	25.3125	16.5	2.9	7.8
TSHCT-3060	25.3125	18.5	3.2	8.4
TSHCT-3248	27.312	12.5	2.37	7.00
TSHCT-3252	27.312	14.5	2.75	7.73
TSHCT-3256	27.312	16.5	3.12	8.45
TSHCT-3260	27.312	18.5	3.50	9.18
TSHCT-3648	31.312	12.5	2.71	8.08
TSHCT-3652	31.312	14.5	3.15	8.91
TSHCT-3656	31.312	16.5	3.58	9.75
TSHCT-3660	31.312	18.5	4.02	10.59
TSHCT-4048	35.312	12.5	3.06	9.15
TSHCT-4052	35.312	14.5	3.55	10.10
TSHCT-4056	35.312	16.5	4.04	11.04
TSHCT-4060	35.312	18.5	4.53	11.99
TSHCT-4448	39.312	12.5	3.41	10.22
TSHCT-4452	39.312	14.5	3.95	11.28
TSHCT-4456	39.312	16.5	4.50	12.34
TSHCT-4460	39.312	18.5	5.05	13.40
TSHCT-4848	43.312	12.5	3.75	11.29
TSHCT-4852	43.312	14.5	4.36	12.46
TSHCT-4856	43.312	16.5	4.96	13.63
TSHCT-4860	43.312	18.5	5.56	14.80

THERMO-TECH 7100 SINGLE-HUNG ORIEL STYLE

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TSHOR-2048	15.312	10.75	1.14	3.78
TSHOR-2052	15.312	12.75	1.35	4.18
TSHOR-2056	15.312	14.75	1.56	4.57
TSHOR-2060	15.312	16.75	1.78	4.96
TSHOR-2448	19.312	10.75	1.44	4.86
TSHOR-2452	19.312	12.75	1.70	5.36
TSHOR-2456	19.312	14.75	1.97	5.86
TSHOR-2460	19.312	16.75	2.24	6.37
TSHOR-2848	23.312	10.75	1.74	5.93
TSHOR-2852	23.312	12.75	2.06	6.54
TSHOR-2856	23.312	14.75	2.38	7.16
TSHOR-2860	23.312	16.75	2.71	7.77
TSHOR-3048	25.3125	12.5	2.1	6.4
TSHOR-3052	25.3125	14.5	2.5	7.1
TSHOR-3056	25.3125	16.5	2.9	7.8
TSHOR-3060	25.3125	18.5	3.2	8.4
TSHOR-3248	27.312	10.75	2.03	7.00
TSHOR-3252	27.312	12.75	2.41	7.73
TSHOR-3256	27.312	14.75	2.79	8.45
TSHOR-3260	27.312	16.75	3.17	9.18
TSHOR-3648	31.312	10.75	2.33	8.08
TSHOR-3652	31.312	12.75	2.77	8.91
TSHOR-3656	31.312	14.75	3.20	9.75
TSHOR-3660	31.312	16.75	3.64	10.59
TSHOR-4048	35.312	10.75	2.63	9.15
TSHOR-4052	35.312	12.75	3.12	10.10
TSHOR-4056	35.312	14.75	3.61	11.04
TSHOR-4060	35.312	16.75	4.10	11.99
TSHOR-4448	39.312	10.75	2.93	10.22
TSHOR-4452	39.312	12.75	3.48	11.28
TSHOR-4456	39.312	14.75	4.02	12.34
TSHOR-4460	39.312	16.75	4.57	13.40
TSHOR-4848	43.312	10.75	3.23	11.29
TSHOR-4852	43.312	12.75	3.83	12.46
TSHOR-4856	43.312	14.75	4.43	13.63
TSHOR-4860	43.312	16.75	5.03	14.80

THERMO-TECH 7600 DOUBLE HUNG

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TDH-2036	14.25	12	1.18	2.37
TDH-2040	14.25	14	1.38	2.71
TDH-2042	14.25	15	1.48	2.88
TDH-2048	14.25	18	1.78	3.40
TDH-2052	14.25	20	1.97	3.74
TDH-2056	14.25	22	2.17	4.09
TDH-2060	14.25	24	2.37	4.43
TDH-2064	14.25	26	2.57	4.78
TDH-2065	14.25	26.5	2.62	4.86
TDH-2072	14.25	30	2.96	5.46
TDH-2436	18.25	12	1.52	3.14
TDH-2440	18.25	14	1.77	3.59
TDH-2442	18.25	15	1.90	3.82
TDH-2448	18.25	18	2.28	4.50
TDH-2452	18.25	20	2.53	4.96
TDH-2456	18.25	22	2.78	5.41
TDH-2460	18.25	24	3.04	5.87
TDH-2464	18.25	26	3.29	6.32
TDH-2465	18.25	26.5	3.35	6.43
TDH-2472	18.25	30	3.80	7.23
TDH-2836	22.25	12	1.85	3.90
TDH-2840	22.25	14	2.16	4.47
TDH-2842	22.25	15	2.31	4.75
TDH-2848	22.25	18	2.78	5.60
TDH-2852	22.25	20	3.09	6.17
TDH-2856	22.25	22	3.39	6.73
TDH-2860	22.25	24	3.70	7.30
TDH-2864	22.25	26	4.01	7.87
TDH-2865	22.25	26.5	4.09	8.01
TDH-2872	22.25	30	4.63	9.00
TDH-3036	24.25	12	2	4.2
TDH-3040	24.25	14	2.3	4.9
TDH-3042	24.25	15	2.52	5.2
TDH-3048	24.25	18	3	6.1
TDH-3052	24.25	20	3.3	6.7
TDH-3056	24.25	22	3.7	7.4
TDH-3060	24.25	24	4	8
TDH-3064	24.25	26	4.3	8.6
TDH-3065	24.25	26.5	4.4	8.7
TDH-3072	24.25	30	5	9.8
TDH-3236	26.25	12	2.18	4.67
TDH-3240	26.25	14	2.55	5.35
TDH-3242	26.25	15	2.73	5.69
TDH-3248	26.25	18	3.28	6.70
TDH-3252	26.25	20	3.64	7.38
TDH-3256	26.25	22	4.01	8.06
TDH-3260	26.25	24	4.37	8.73
TDH-3264	26.25	26	4.73	9.41
TDH-3265	26.25	26.5	4.83	9.58
TDH-3272	26.25	30	5.46	10.76
TDH-3636	30.25	12	2.52	5.44
TDH-3640	30.25	14	2.94	6.23
TDH-3642	30.25	15	3.15	6.62
TDH-3648	30.25	18	3.78	7.80
TDH-3652	30.25	20	4.20	8.59
TDH-3656	30.25	22	4.62	9.38
TDH-3660	30.25	24	5.04	10.17
TDH-3664	30.25	26	5.46	10.96
TDH-3665	30.25	26.5	5.57	11.15
TDH-3672	30.25	30	6.30	12.53
TDH-4036	34.25	12	2.85	6.21
TDH-4040	34.25	14	3.32	7.11
TDH-4042	34.25	15	3.56	7.55
TDH-4048	34.25	18	4.28	8.90
TDH-4052	34.25	20	4.75	9.80
TDH-4056	34.25	22	5.23	10.70
TDH-4060 E	34.25	24	5.70	11.60
TDH-4064 E	34.25	26	6.18	12.50
TDH-4065 E	34.25	26.5	6.30	12.73
TDH-4072 E	34.25	30	7.13	14.30

E= Denotes 5.7 square feet or greater clear opening. Verify local or state egress opening sizes with your local building inspector.



Energy Star® qualified in all four climate zones.

LIGHT, VENTILATION & EGRESS DATA

OPENING SPECIFICATIONS

THERMO-TECH 7600 DOUBLE HUNG

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TDH-4436	38.25	12	3.16	6.97
TDH-4440	38.25	14	3.71	7.98
TDH-4442	38.25	15	3.98	8.49
TDH-4448	38.25	18	4.78	10.00
TDH-4452	38.25	20	5.31	11.01
TDH-4456	38.25	22	5.84	12.03
TDH-4460 E	38.25	24	6.37	13.04
TDH-4464 E	38.25	26	6.90	14.05
TDH-4465 E	38.25	26.5	7.03	14.30
TDH-4836	42.25	12	3.52	7.74
TDH-4840	42.25	14	4.10	8.86
TDH-4842	42.25	15	4.40	9.42
TDH-4848	42.25	18	5.28	11.11
TDH-4852	42.25	20	5.86	12.23
TDH-4856	42.25	22	6.45	13.35
TDH-4860 E	42.25	24	7.04	14.47
TDH-4864 E	42.25	26	7.62	15.59
TDH-4865 E	42.25	26.5	7.77	15.87

E= Denotes 5.7 square feet or greater clear opening. Verify local or state egress opening sizes with your local building inspector.

THERMO-TECH 7600 DOUBLE-HUNG COTTAGE STYLE

Unit Number	Egress Vent Size*		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TDHCT-2048	14.25	12.5	1.23	3.40
TDHCT-2052	14.25	14.5	1.43	3.74
TDHCT-2056	14.25	16.5	1.63	4.09
TDHCT-2060	14.25	18.5	1.83	4.43
TDHCT-2448	18.25	12.5	1.58	4.50
TDHCT-2452	18.25	14.5	1.83	4.96
TDHCT-2456	18.25	16.5	2.09	5.41
TDHCT-2460	18.25	18.5	2.34	5.87
TDHCT-2848	22.25	12.5	1.93	5.60
TDHCT-2852	22.25	14.5	2.24	6.17
TDHCT-2856	22.25	16.5	2.54	6.73
TDHCT-2860	22.25	18.5	2.85	7.30
TDHCT-3048	24.25	12.5	2.1	6.1
TDHCT-3052	24.25	14.5	2.4	6.7
TDHCT-3056	24.25	16.5	2.7	7.4
TDHCT-3060	24.25	18.5	3.1	8
TDHCT-3248	26.25	12.5	2.27	6.70
TDHCT-3252	26.25	14.5	2.64	7.38
TDHCT-3256	26.25	16.5	3.00	8.06
TDHCT-3260	26.25	18.5	3.37	8.73
TDHCT-3648	30.25	12.5	2.62	7.80
TDHCT-3652	30.25	14.5	3.04	8.59
TDHCT-3656	30.25	16.5	3.46	9.38
TDHCT-3660	30.25	18.5	3.88	10.17
TDHCT-4048	34.25	12.5	2.97	8.90
TDHCT-4052	34.25	14.5	3.44	9.80
TDHCT-4056	34.25	16.5	3.92	10.70
TDHCT-4060	34.25	18.5	4.40	11.60
TDHCT-4448	38.25	12.5	3.31	10.00
TDHCT-4452	38.25	14.5	3.84	11.01
TDHCT-4456	38.25	16.5	4.37	12.03
TDHCT-4460	38.25	18.5	4.91	13.04
TDHCT-4848	42.25	12.5	3.66	11.11
TDHCT-4852	42.25	14.5	4.25	12.23
TDHCT-4856	42.25	16.5	4.84	13.35
TDHCT-4860	42.25	18.5	5.42	14.47

*Vent size calculations reflect bottom sash only!

THERMO-TECH 7600 DOUBLE-HUNG ORIEL STYLE

Unit Number	Egress Vent Size*		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
TDHOR-2048	14.25	10.75	1.08	3.40
TDHOR-2052	14.25	12.75	1.26	3.74
TDHOR-2056	14.25	14.75	1.45	4.09
TDHOR-2060	14.25	16.75	1.65	4.43
TDHOR-2448	18.25	10.75	1.36	4.50
TDHOR-2452	18.25	12.75	1.65	4.96
TDHOR-2456	18.25	14.75	1.86	5.41
TDHOR-2460	18.25	16.75	2.12	5.87
TDHOR-2848	22.25	10.75	1.66	5.60
TDHOR-2852	22.25	12.75	1.97	6.17
TDHOR-2856	22.25	14.75	2.27	6.73
TDHOR-2860	22.25	16.75	2.58	7.30
TDHOR-3048	24.25	10.75	1.8	6.1
TDHOR-3052	24.25	12.75	2.1	6.7
TDHOR-3056	24.25	14.75	2.4	7.4
TDHOR-3060	24.25	16.75	2.8	8
TDHOR-3248	26.25	10.75	1.95	6.70
TDHOR-3252	26.25	12.75	2.32	7.38
TDHOR-3256	26.25	14.75	2.68	8.06
TDHOR-3260	26.25	16.75	3.05	8.73
TDHOR-3648	30.25	10.75	3.25	7.80
TDHOR-3652	30.25	12.75	2.67	8.59
TDHOR-3656	30.25	14.75	2.99	9.38
TDHOR-3660	30.25	16.75	3.51	10.17
TDHOR-4048	34.25	10.75	2.55	8.90
TDHOR-4052	34.25	12.75	3.03	9.80
TDHOR-4056	34.25	14.75	3.38	10.70
TDHOR-4060	34.25	16.75	3.98	11.60
TDHOR-4448	38.25	10.75	2.85	10.00
TDHOR-4452	38.25	12.75	3.38	11.01
TDHOR-4456	38.25	14.75	3.91	12.03
TDHOR-4460	38.25	16.75	4.44	13.04
TDHOR-4848	42.25	10.75	3.15	11.11
TDHOR-4852	42.25	12.75	3.74	12.23
TDHOR-4856	42.25	14.75	4.32	13.35
TDHOR-4860	42.25	16.75	4.91	14.47

*Vent size calculations reflect bottom sash only!

THERMO-TECH SLIDING PATIO DOORS

Unit Number	Egress Vent Size		Vent Area Sq. Ft.	Daylight Area Sq. Ft.
	Width	Height		
CPD-5068	21.5	75.5	11.27	20.34
CPD-6068	27.5	75.5	14.41	25.90
CPD-6568	29.875	75.5	15.6	28.2
CPD-6768*	31.875	75.5	16.7	29.1
CPD-8068	39.5	75.5	20.71	37.00
CPD-50610	21.5	77.5	11.57	20.96
CPD-60610	27.5	77.5	14.80	26.68
CPD-65610	29.875	77.5	16	29
CPD-67610*	31.875	77.5	17.1	30
CPD-80610	39.5	77.5	21.25	38.12
CPD-9068	27.5	75.5	14.41	26.68
CPD-12068	56.25	75.5	29.49	51.80
CPD-90610	27.5	77.5	14.80	26.68
CPD-120610	56.25	77.5	30.27	53.36

*32" clear opening width available when ordered with C handle. Specify 32" clear opening at time of order.



LIGHT, VENTILATION & EGRESS DATA

OPENING SPECIFICATIONS

THERMO-TECH 2545 DIRECT-SET PICTURE WINDOWS

Unit Number	Daylight Area Sq. Ft.	Unit Number	Daylight Area Sq. Ft.	Unit Number	Daylight Area Sq. Ft.
DS-1830	2.63	DS-4048	11.20	DS-6024	7.97
DS-1836	3.23	DS-4052	12.21	DS-6028	9.54
DS-2024	2.31	DS-4056	13.23	DS-6032	11.10
DS-2030	2.99	DS-4060	14.24	DS-6036	12.67
DS-2036	3.68	DS-4064	15.25	DS-6040	14.24
DS-2040	4.13	DS-4072	17.27	DS-6042	15.02
DS-2042	4.36	DS-4220	4.36	DS-6048	17.37
DS-2048	5.04	DS-4224	5.42	DS-6052	18.93
DS-2052	5.50	DS-4228	6.49	DS-6056	20.50
DS-2056	5.95	DS-4232	7.56	DS-6060	22.07
DS-2060	6.41	DS-4420	4.59	DS-6064	23.63
DS-2064	6.86	DS-4424	5.71	DS-6072	26.76
DS-2072	7.77	DS-4428	6.83	DS-6420	6.86
DS-2424	2.88	DS-4432	7.95	DS-6424	8.54
DS-2436	4.58	DS-4436	9.07	DS-6428	10.21
DS-2440	5.14	DS-4440	10.19	DS-6432	11.89
DS-2442	5.42	DS-4442	10.75	DS-6436	13.57
DS-2448	6.27	DS-4448	12.44	DS-6440	15.25
DS-2452	6.84	DS-4452	13.56	DS-6442	16.08
DS-2456	7.41	DS-4456	14.68	DS-6448	18.60
DS-2460	7.97	DS-4460	15.77	DS-6452	20.28
DS-2464	8.54	DS-4464	16.92	DS-6456	21.95
DS-2472	9.67	DS-4472	19.17	DS-6460	23.63
DS-2824	3.44	DS-4820	5.04	DS-6464	25.31
DS-2836	5.48	DS-4824	6.27	DS-6472	28.66
DS-2840	6.15	DS-4828	7.51	DS-6836	14.47
DS-2842	6.49	DS-4832	8.74	DS-6840	16.26
DS-2848	7.51	DS-4836	9.97	DS-6842	17.15
DS-2852	8.18	DS-4840	11.20	DS-6848	19.83
DS-2856	8.86	DS-4842	11.82	DS-6852	21.62
DS-2860	9.54	DS-4848	13.67	DS-6856	23.41
DS-2864	10.21	DS-4852	14.90	DS-6860	25.20
DS-2872	11.57	DS-4856	16.13	DS-6864	26.99
DS-3224	4.01	DS-4860	17.37	DS-6872	30.56
DS-3236	6.37	DS-4864	18.60	DS-7220	7.77
DS-3240	7.16	DS-4872	21.07	DS-7224	9.67
DS-3242	7.56	DS-5220	5.50	DS-7228	11.57
DS-3248	8.74	DS-5224	6.84	DS-7232	13.47
DS-3252	9.53	DS-5228	8.18	DS-7236	15.37
DS-3256	10.32	DS-5232	9.53	DS-7240	17.27
DS-3260	11.10	DS-5236	10.87	DS-7242	18.22
DS-3264	11.89	DS-5240	12.21	DS-7248	21.07
DS-3272	13.47	DS-5242	12.89	DS-7252	22.96
DS-3620	3.68	DS-5248	14.91	DS-7256	24.86
DS-3624	4.58	DS-5252	16.25	DS-7260	26.76
DS-3628	5.48	DS-5256	17.59	DS-7264	28.66
DS-3632	6.37	DS-5260	18.93	DS-7272	32.46
DS-3636	7.27	DS-5264	20.28	DS-8436	18.07
DS-3640	8.17	DS-5272	22.96	DS-8440	20.30
DS-3642	8.62	DS-5620	5.95	DS-8442	21.41
DS-3648	9.97	DS-5624	7.41	DS-8448	24.76
DS-3652	10.87	DS-5628	8.86	DS-8452	27.00
DS-3656	11.77	DS-5632	10.32	DS-8456	29.23
DS-3660	12.67	DS-5636	11.77	DS-8460	31.46
DS-3664	13.57	DS-5640	13.23	DS-8464	33.69
DS-3672	15.37	DS-5642	13.95	DS-8472	38.16
DS-4020	4.13	DS-5648	16.13	DS-9636	20.76
DS-4024	5.14	DS-5652	17.59	DS-9640	23.33
DS-4028	6.15	DS-5656	19.04	DS-9642	24.61
DS-4032	7.16	DS-5660	20.50	DS-9648	26.46
DS-4036	8.17	DS-5664	21.95	DS-9652	31.03
DS-4040	9.18	DS-5672	24.86	DS-9656	33.59
DS-4042	9.69	DS-6020	6.41	DS-9660	36.16

THERMO-TECH 2630 FIXED CASEMENT WINDOWS

Unit Number	Daylight Area Sq. Ft.	Unit Number	Daylight Area Sq. Ft.
FC-2024	1.58	FC-4856	14.10
FC-2036	2.69	FC-4860	15.25
FC-2040	3.05	FC-5220	4.16
FC-2042	3.24	FC-5224	5.42
FC-2048	3.79	FC-5228	6.67
FC-2052	4.16	FC-5232	7.93
FC-2056	4.53	FC-5236	9.19
FC-2060	4.89	FC-5240	10.44
FC-2424	2.06	FC-5242	11.07
FC-2436	3.50	FC-5248	12.96
FC-2440	3.98	FC-5252	14.21
FC-2442	4.22	FC-5256	15.47
FC-2448	4.94	FC-5260	16.73
FC-2452	5.42	FC-5620	4.53
FC-2456	5.89	FC-5624	5.89
FC-2460	6.37	FC-5628	7.26
FC-2824	2.54	FC-5632	8.63
FC-2836	4.31	FC-5636	10.00
FC-2840	4.90	FC-5640	11.37
FC-2842	5.20	FC-5642	12.05
FC-2848	6.08	FC-5648	14.10
FC-2852	6.67	FC-5652	15.47
FC-2856	7.26	FC-5656	16.84
FC-2860	7.85	FC-5660	18.21
FC-3224	3.02	FC-6020	4.89
FC-3236	5.12	FC-6024	6.37
FC-3240	5.83	FC-6028	7.85
FC-3242	6.18	FC-6032	9.33
FC-3248	7.23	FC-6036	10.81
FC-3252	7.93	FC-6040	12.29
FC-3256	8.63	FC-6042	13.03
FC-3260	9.33	FC-6048	15.25
FC-3620	2.69	FC-6052	16.73
FC-3624	3.50	FC-6056	18.21
FC-3628	4.31	FC-6060	19.69
FC-3632	6.12	FC-6420	5.26
FC-3636	5.94	FC-6424	6.85
FC-3640	6.75	FC-6428	8.44
FC-3642	7.16	FC-6432	10.03
FC-3648	8.37	FC-6436	11.62
FC-3652	9.19	FC-6440	13.21
FC-3656	10.00	FC-6442	14.00
FC-3660	10.81	FC-6448	16.39
FC-4020	3.05	FC-6452	17.99
FC-4024	3.98	FC-6456	19.58
FC-4028	4.90	FC-6460	21.17
FC-4032	5.83	FC-6836	12.44
FC-4036	6.75	FC-6840	14.14
FC-4040	7.67	FC-6842	14.99
FC-4042	8.14	FC-6848	17.54
FC-4048	9.52	FC-6852	19.24
FC-4052	10.44	FC-6856	20.94
FC-4056	11.37	FC-6860	22.64
FC-4060	12.29	FC-7220	6.00
FC-4220	3.24	FC-7224	7.81
FC-4224	4.22	FC-7228	9.62
FC-4228	5.20	FC-7232	11.44
FC-4232	6.18	FC-7236	13.25
FC-4420	3.42	FC-7240	15.06
FC-4424	4.86	FC-7242	15.97
FC-4428	5.49	FC-7248	18.69
FC-4432	6.53	FC-7252	20.50
FC-4436	7.56	FC-7256	22.31
FC-4440	8.60	FC-7260	24.12
FC-4442	9.11	FC-8436	15.69
FC-4448	10.67	FC-8440	17.83
FC-4452	11.70	FC-8442	18.91
FC-4456	12.74	FC-8448	22.12
FC-4460	13.77	FC-8452	24.27
FC-4820	3.79	FC-8456	26.42
FC-4824	4.94	FC-8460	28.56
FC-4828	6.08	FC-9636	18.12
FC-4832	7.23	FC-9640	20.60
FC-4836	8.37	FC-9642	21.84
FC-4840	9.52	FC-9648	25.56
FC-4842	10.09	FC-9652	28.04
FC-4848	11.81	FC-9656	30.52
FC-4852	12.96	FC-9660	33.00



Energy Star® qualified in all four climate zones.